

The WAVE ID Analyze is an intelligent portable tool used for identifying the proximity and contactless smart card technology in use at an organization and helps determine the compatible rf IDEAS® dual frequency or single frequency reader.



With hundreds of different card types in use worldwide, the WAVE ID Analyze simplifies the process of matching the reader to card type. This eliminates the often lengthy and frustrating process of identifying the card. Using the WAVE ID Analyze the user, solution provider or integrator identifies the card type and then determines the compatible reader using the Card/Reader Guide provided in the kit.

Quick and easy card identification

The WAVE ID Analyze is easily connected to a computer via the USB port. As the card is placed on the WAVE ID Analyze, results are instantaneously sent as keystrokes to Microsoft® Notepad or the text field of any other application. No additional software is required and the WAVE ID Analyze is compatible with nearly all computer operating systems that support USB keyboard devices.

Identify which reader is right for you

The results displayed include the card type, data size and raw data (card CSN or UID) in hexadecimal format. A compact card guide included with the kit allows the user to match the output to a compatible rf IDEAS® reader device and provides the rf IDEAS® Config Utility Card Type Setting in order to read the card with a WAVE ID® Plus reader.

| Card Type | Frequency | Card Markings | Compatible Readers | WAVE ID Config Utility Card Type Setting for WAVE ID Plus Readers |
|--------------------|-----------|--------------------|---|---|
| HID® iCLASS® Seos® | 13.56 MHz | HID® iCLASS® Seos® | RDR-300x RDR-800x RDR-701x RDR-708xCxx | HID® Seos® |

Below is a representation of the output format for an HID® Seos® card:

Please visit www.rfIDEAS.com/analyze for information on rf IDEAS reader products compatible with your card.

Card Type: HID SEOS UID
Data Length: 26-Bits
Raw Data(Hex): 00042ee2

This compact, convenient sales tool is user-friendly and highly reliable. Just like the rf IDEAS WAVE ID Plus readers, the tool supports the most number of card types worldwide of all the comparable solutions on the market.



Trust begins here.™

WAVE ID® Analyze Card Analyzer Kit

| STANDARD FEATURES | |
|---|---|
| Kit Model Number* | KT-8XX88AQU-C16 |
| Contents of Kit | WAVE ID® Analyze Model #RDR-8XX88AQU-C16 Card/Reader Guide Quick Start Guide HID® Prox key fob iCLASS® ISO card |
| PHYSICAL CHARACTERISTICS | |
| Dimensions of analyzer | Length 3.6" (9.02 cm) Width 2.1" (5.21 cm) Height 0.6" (1.60 cm) |
| Weight | 4.5 ounces (127.57g) |
| Housing Color | Quartz White |
| Indicators | LED indicator; beeper |
| Power Supply | USB Powered |
| ENVIRONMENT | |
| Operating Temperature Range | -22° to 150°F (-30° to 65°C) |
| Operating Humidity Range | 5% to 95% relative humidity, non-condensing |
| Storage Temperature Range | -40° to 185°F (-40° to 85°C) |
| OTHER | |
| Certifications <i>(Please contact rf IDEAS for information about other global certifications)</i> | FCC-United States; CE Mark-Europe; RCM-Australia; IC-Industry Canada; UL Environmental: RoHS, REACH |
| Compatible Operating Systems | Windows XP®, 7®, 8®, 10® and Linux Ubuntu 12.04 |

*Note: "X" in the part number represents an option.